

Product certificate KIP-065865/01

Issued 2011-12-15

Replaces

Page 1 of 2

Water pressure reducing valves

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by


F.A.R.G. srl

complying with the technical specifications as laid down in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate, on delivery, may be relied upon to comply with Kiwa evaluation guideline

BRL-K14004/ 01: "Water reducing valves and combination water pressure reducing valves".

as well as to:

EN 1567: Water reducing valves and combination water pressure reducing valves"



Bouke Meekma
Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V
Sir W. Churchill-laan 273
Postbus 70
2280 AB RIJSWIJK
The Netherlands

Tel. +31 70 414 44 00
Fax +31 70 414 44 20
E-mail info@kiwa.nl
www.kiwa.nl



Supplier

F.A.R.G. s.r.l.
Via Cesare Battisti 77
28045 INVORIO
Italy
Telephone : +39 0322 255193
Telefax: +39 0322 259487
Website : www.farg.it
e-mail: info@farg.it

**Certification process
consists of initial and
regular inspection of:**

- quality system
- product

Water pressure reducing valves

Products specification

The products mentioned below belong to this certificate

Water pressure reducing valves

Model 490, DN 12, DN 15, DN 20 (Minirid)
Model 500, DN 15, DN 20 (Mignon)
Model 501, DN 15, DN 20, DN 25, (Normale)
Model 502, DN 15, DN 20, DN 25, DN 32, DN 40, DN 50
Model 504, DN 15, DN 20, DN 25, DN 32, DN 40, DN 50
Model 505, DN 15, DN 20, DN 25, DN 32, DN 40, DN 50

Application and use

Water reducing valves and combination water pressure reducing valves of nominal size DN 8 to DN 100 for inlet pressures that not exceed 1.600 kPa and a temperature that does not exceed 30°C for cold water application and 80°C for hot water application. Except when stated otherwise by the manufacturer the valves can be applied for both temperature applications.

Marking

The Kiwa[®]-mark products are marked with the wordmark "KIWA".

Place of the mark: on the body

Compulsory specifications:

- Name or logo of the manufacturer
- DN
- Set pressure for non-adjustable valves
- An arrow for the direction of flow
- Outlet pressure for special cases
- DR for dezincification materials

Method of marking:

- Non-erasable;
- visible after assembly.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

-

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.